



Smart 2430V3 Zero Client

Profile

Smart 2430 V3 is Zero client based on quad-core ARM Cortex A53 SOC(System on Chip) CPU and embedded Linux OS. It delivers deeply optimized RDP 10 (RemoteFX) client, and supports Windows 7/8/10, as well as Multipoint and Windows servers, etc.



Smart 2430V3 Zero Client

Features

HD Experience

Up to 1920*1080p 32bpp display, Video redirection, Supports remotefx vGPU virtualization with 3D experience.USS redirection, Video Redirection for SMB,Video Redirection forVDI.

Free VDClass Software

VDClass is an easy and simple e-class software, which could broadcast the teacher's desktop to all the Zero clients in LAN.

Desktop Broadcasting

SMART 2430 V3 is a Zero client integrated the receiver of DesktopCaster, which could receive the video stream from DesktopCaster. In most cases, the DesktopCaster software could be used to broadcast the teacher s Windows desktop directly to zero clients instead of the student's remote desktops.

Free Management Software

TCM(Zero Client Management System) is a free software to manage all the Smart 2430 V3 Zero client. It delivers many features to control the devices over network.



Connectivity



- 1 Power Button
- 2 Multimedia Ports
- 3 USB 2.0 Ports
- 4 Kensington Lock
- 5 USB 2.0 Ports

- 6 DC in
- 7 LAN Port
- 8 USB 2.0 Ports
- 9 HDMI Ports
- 10 VGA Port



Specification



| | |
|----------------------------|--|
| Processor | Cortex A53 Quad-core 1.5 Ghz Soc(System on Chip) |
| Protocol | RDP10 |
| System Memory | 1GB SOC |
| Storage | 8GB eMMC |
| Display | Resolution Support up to 1920 X 1200 @ 60 Hz with 24/32 bit color |
| Supported OS | Windows 7/8/10, Linux OS Windows Multi Point Server 2008 R2/2012 R2/2016 R2, 2019 |
| Multimedia Support | Hardware-accelerated 2D graphics, hardware-accelerated video support for most media formats on stand-alone media player applications and browser-based video |
| Output | 1xVGA, 1xHDMI port, 5xUSB port, Input 1xDC port, 1xRJ45 port, 3.5mm stereo audio jacks for head hone & micro hone. |
| Network | 10/100/1000 Base-T Fast Ethernet, RJ-45 |
| Size | 107 X 107 X 28mm |
| Weight | 0.25KG |
| Rated output current (max) | 3A |
| Output voltage | +5V DC |
| Operating temperature | 0° ~ 35° |
| Operating humidity (Rh) | 10% ~ 90% (non-condensing) |
| Operating voltage range | 100 ~ 240 VAC |
| Rated line frequency | 50 ~ 60Hz |
| Cooling | Fan-less Convection |





Contact

Apurva Computers Technologies Pvt. Ltd

Corporate Office: 1210, 12th Floor, One World West, Bopal Approach BRTS Bus stop, Near Vakil Saheb Bridge, Bopal, Ahmedabad-380058 (Gujarat) India.

Registered Office: 2nd Floor, Manivir Complex, Vitthal Press Road, Surendranagar-363001 (Gujarat) India.

Contact: +91 98242 08215 / 98242 08213 / 93746 51621 / 93769 15048

Email: sales@smartstation.in

Website: www.smartstation.in

